



TOLERANCE IS ±0.05

- NOTES:
- MATERIAL:
 - HOUSING: THERMOPLASTIC RATING UL94V-0
 - CONTACT: COPPER ALLOY
 - PAD: COPPER ALLOY
 - FINISH:
 - CONTACT: 50μMIN GOLD PLATED ON CONTACT AREA, GOLD FLASH PLATED ON SOLDERTAIL AREA
 - 2-PAD: 80μMIN, MATTE TIN PLATING OVER ALL
 - PRODUCT SPECIFICATIONS:
 - CURRENT RATING: 1.0A/DC MAX.
 - VOLTAGE RATING: 100V/DC MAX.
 - CONTACT RESISTANCE: 50mΩ ILLUMINM MAX.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC
 - INSULATION RESISTANCE: 500 MΩ EGΩHMS MIN
 - PRODUCT COMPLIANCE WITH ROHS DIRECTIVE

Bill Of Materials:

No.	TITLE	MATERIAL	FINISH(OR COLOR)	NO.
1	HOUSING	LCP+30%GF,UL94 V-0	BLACK	1
2	TERMINAL	C5210,T=0.10mm		4
3	GROUND SLICE	BRASS(C2680),T=0.20mm	TIN 80μPLATED	2

UNITS: mm		CSCONN		CSCONN PRECISE ELECTRONICS CO.,LTD	
GENERAL TOLERANCE	X. ±5°	PART NO.(INTENDED USE)	CBA2504355003	TITLE:	BATTERY 4P 2.5MM H=3.55MM 沉板式
	0. X±0.25	APPD:		DWG NO.	BATTERY
	X. 1±2°	CHKD:	Skilia	SCALE	1:1
	XX. ±1°	DR:	Kitty	SHEET	1 OF 1
	0. XXX±0.1			REV	A

