


RECOMMEND PCB LAYOUT  
DEFAULT TDL:±0.05



- NOTES:
1. MATERIAL: HOUSING: HIGH-TEMP PLASTIC UL 94V-0; CONTACT: COPPER ALLOY; PEG: COPPER ALLOY;
  2. PLATING: CONTACT: GOLD OR TIN PLATED ON NICKEL OVERALL. PEG: TIN PLATED ON NICKEL OVERALL.
  3. RATING: CURRENT RATING: 0.3A AC/DC VOLTAGE RATING: 50V AC/DC TEMPERATURE RANGE: -25~+85D;

PIN NO.	A	B	C
10	4.00	3.74	1.60
24	6.80	6.54	4.40
30	8.00	7.74	5.60
40	10.00	9.74	7.60
50	12.00	11.74	9.60
60	14.00	13.74	11.60

- UNITS: mm
- GENERAL TOLERANCE
- X. ±5° 0.XX±0.25
- X.1±2° 0.XX±0.2
- XX.±1° 0.XXX±0.1
- PART NO. (INTENDED USE)  
CBT-0410XXM-09
- APPD:  
CHKD: Skilla
- DR: Kitty
- TITLE: BTB 0.4MM XP MALE H=0.9MM
- DWG NO. BTB
- SCALE 1:1
- SHEET 1 OF 1
- REV A

**CSCONN**

CSCONN PRECISE ELECTRONICS CO., LTD

TITLE: BTB 0.4MM XP MALE H=0.9MM

DWG NO. BTB

SCALE 1:1

SHEET 1 OF 1

REV A

E

1

2

3

4

5

6

7

8

D

C

B

A

1

2

3

4

5

6

7

8

D

C

B

A

E