



RECOMMENDED PCB LAYOUT



MATING SECTION

TABLE:

PIN NO.	A	B	C
24	5.90	4.40	2.40
30	7.10	5.60	3.60
40	9.10	7.60	5.60
50	11.10	9.60	7.60
60	13.10	11.60	9.60
70	15.10	13.60	11.60

- NOTES:
1. MATERIAL: HOUSING: HIGH-TEMP PLASTIC(WITHOUT HALOGEN),
UL 94V-0;
 2. PLATING: CONTACT: COPPER ALLOY;
CONTACT: GOLD OR TIN PLATED
ON NICKEL OVERALL.
 3. RATING: VOLTAGE RATING: 100V AC/DC
TEMPERATURE RANGE: -25~+85D;

UNITS: mm		CSCONN		CSCONN PRECISE ELECTRONICS CO.,LTD	
GENERAL TOLERANCE		PART NO.(INTENDED USE)		TITLE:	
X. ° ±5°	0. X±0.25	CBT-0410XXM-15		BTB 0.4MM XP MALE H=1.5MM	
X. 1±2°	0. XX±0.2	APPD:		DWG NO. BTB	
XX ±1°	0. XXX±0.1	CHKD: Skilla		SCALE	
		DR: Kitty		1:1	
				SHEET	
				1 OF 1	
				REV	
				A	