



RECOMMENDED PCB LAYOUT

Pin 位	A	B	C	Pin 位	A	B	C
1	3	5.06	11	23	22	24.06	30
2	4	6.06	12	24	23	25.06	31
3	5	7.06	13	25	24	26.06	32
4	6	8.06	14	26	25	27.06	33
5	7	9.06	15	27	26	28.06	34
6	8	10.06	16	28	27	29.06	35
7	9	11.06	17	29	28	30.06	36
8	10	12.06	18	30	29	31.06	37
9	11	13.06	19	31	30	32.06	38
10	12	14.06	20	32	31	33.06	39
11	13	15.06	21	33	32	34.06	40
12	14	16.06	22	34	33	35.06	41
13	15	17.06	23	35	34	36.06	42
14	16	18.06	24	36	35	37.06	43
15	17	19.06	25	37	36	38.06	44
16	18	20.06	26	38	37	39.06	45
17	19	21.06	27	39	38	40.06	46
18	20	22.06	28	40	39	41.06	47
19	21	23.06	29				
20	22						
21	23						
22	24						

**SPECIFICATION**

1. Material:  
 Housing: HIGH-TEMP Plastic,UL94V-0,color:Natural.  
 Lock: HIGH-TEMP Plastic,UL94V-0,color:black.  
 Contacts: Copper alloy.

2. Electrical Characteristics:  
 Current rating: 0.5A(max).  
 Voltage rating: 50V(max).  
 Operating Temperature: -25C~+85C.  
 Insulation resistance: 500M ohms min. at 500V DC  
 Dielectric withstanding voltage: 500V AC/minute.  
 Contact resistance: 30m ohms max.

APPLICABLE FPC

UNITS: mm	<b>CSCONN</b>		CSCONN PRECISE ELECTRONICS CO.,LTD	
GENERAL TOLERANCE	PART NO. (INTENDED USE)	TITLE:	FPC 1.0MM XP SMT 立贴带锁正脚位	
X. ±5° 0.X±0.25	CFP-1024XL-T	DWG NO.	FPC	
X.1±2° 0.XX±0.2	APPD:	SCALE	SHEET	REV
XX. ±1° 0.XXX±0.1	CHKD: Skilla	1:1	1 OF 1	A
	DR: Kitty			