


RECOMMENDED P.C.B. LAYOUT

Specifications:

Electrical:

- 1.Character Impedance: 50Ω
- 2.Rating Voltage: 60V AC
- 3.Contact Resistance
 - 3.1Inner Contact:25 mΩ max
 - 3.2Outer Contact:15 mΩ max
- 4.Withstanding Voltage: 200V AC 1min
- 5.Insulation Resistance:500MΩ
- 6.Operate Temperature: -40℃~+90℃
- 7.Operate Humidity: 95% max
- 8.Frequency Range: 0~6GHz

ITEM	PART NAME	Q'TY	MATERIAL/FINISH
③	SHELL	1	COPPER ALLOY/Ag PLATED OVER Ni
②	CONTACT	1	COPPER ALLOY/GOLD PLATED OVER Ni
①	HOUSING	1	HIGHT TEMP. PLASTIC UL94V-0/BLACK

UNITS:		CSCONN	CSCONN PRECISE ELECTRONICS CO.,LTD			
mm GENERAL TOLERANCE			PART NO.(INTENDED USE) CRF3031125002	TITLE: MINI RF 1.25H 三焊脚		
X. ° ±5°	0. X±0.25	APPD:	DWG NO. RF			
X. 1±2°	0. XX±0.2	CHKD: Skila		SCALE	SHEET	REV
XX. ±1°	0. XXX±0.1	DR: Kitty		1:1	1 OF 1	A