


RECOMMENDED PCB LAYOUT  
TOLERANCES ±0.05

NOTES:  
1. MATERIAL, SEE TABLE A



Pin No	Name	Type
1	DAT2	I/O/PP
2	CD/DATS	I/O/PP
3	CMD	PP
4	VDD	S
5	CLK	I
6	VSS	S
7	DAT0	I/O/PP
8	DAT1	I/O/PP

ITEM	NAME	Q'TY/EACH	MATERIAL/FINISHED
3	PAD	2	COPPER ALLOY SN PLATED
2	CONTACT	8	COPPER ALLOY MATING AREA Au PLATED
1	HOUSING	1	THERMOPLASTIC UL94V-0, BLACK

UNITS: mm		<b>CSCONN</b>		CSCONN PRECISE ELECTRONICS CO.,LTD	
GENERAL TOLERANCE		PART NO.(INTENDED USE)		TITLE:	
X. ±5°	0.X±0.25	CTP1108118190		T-FLASH CARD 抽屜式	
X.1±2°	0.XX±0.2	APPD:		DWG NO.	
X.X±1°	0.XXX±0.1	CHKD: Skila		T-FLASH	
		DR: Kitty		SCALE	
				1:1	
				SHEET	
				1 OF 1	
				REV	
				A	

