



NOTES:

- Housing: Thermoplastics, UL94V-0
- Contact: Copper Alloy
- Shell: Copper Alloy/Steel
- Voltage Current Rating: 1.5 AMP, 30V AC
- Insulation Resistance: 1000M $\Omega$  Min.
- Contact Resistance: 30 M $\Omega$  Max.
- Dielectric Withstanding Voltage: 500W AC
- Temperature Range: -35°C to +85°C
- Insulator color: Black/White
- Plastic material: PBT/LCP/Others
- Shell finish: Nickel plated/Tin-Lead plated
- Mechanical:
  - Mating Force: 3.5KG MAX
  - Umating Force: 0.7 KG MIN.

PCB LAYOUT

UNITS: mm		<b>CSCONN</b>		CSCONN PRECISE ELECTRONICS CO., LTD	
GENERAL TOLERANCE		PART NO. (INTENDED USE)		TITLE: USB A/F 4P SMT	
X. ° ±5°	0. X ±0.25	CUS-0445F-T		DWG NO. USB	
X.1 ±2°	0. XX ±0.2	APPD:		SCALE SHEET REV	
XX. ±1°	0. XXX ±0.1	CHKD: Skilla		1:1 1 OF 1 A	
		DR: Kitty			